









The following pages contain just a few examples of the new products available at BSP SALES CENTRE in 2024. Also included is a preview of the new '24/25 catalogue that will also be available to pre-order very soon.

You can see from the list of brands available that our stock range will be quite extensive and all supplied with the same excellent service that our customers enjoy already. Our complimentary conversion table is free to download here

For further information on any of these examples or any general queries, please call our sales team on (029) 2046 5451







*New Core Stock

Prestige Air Hammer & De-Scaling Set





*New Core Stock

APT561

Needle Scaler Straight







Steel Hose Reel, Air Hose, Dual Arm, 15m of 3/8" Hose, 1/4" Fittings

SKU: HRA4P01

Steel Hose Reel, Air Hose, Dual Arm, 15m of 1/2" Hose, 1/2" Fittings

SKU: HRA4P02

Available November 2023

Introducing PCI's new heavy duty, dual arm, retractable air hose reel, specifically designed for use with compressed air in garages, workshops, and industrial applications.

This Steel Hose Reel features auto retract as standard, the 15m hose is neatly and effortlessly stored with no kinks or tangles.

Life tested to 8,000 cycles, our new steel reels feature 4 non-snag rollers, an adjustable arm guide and NBR superior strength hose for reduced hose wear.





BSP3HP150L-BD14

No Nonesense Ready to Run Workhorse
150ltr air receiver & Wheel-mounted
Belt-driven transmission
Twin cylinder splash oil-lubricated pump
Heavy-duty brushless induction motor







BSP3HP200L-BD14

No Nonesense Ready to Run Workhorse

200Ltr air receiver & Wheel-mounted

Belt-driven transmission

Twin cylinder splash oil-lubricated pump

Heavy-duty brushless induction motor









SIP VSDD 5.5kW 10bar 200ltr Screw Compressor

BSP8260

The SIP VSDD 5.5kW 10bar 200ltr 400v Rotary Screw Compressor is a variable speed, direct drive rotary screw compressor. This 4th generation compressor is designed for continuous use or where multiple operators require compressed air at one time.

With a motor output of 5.5kW, this compressor can meet high-demand air requirements and optimise energy usage. Fitted with a 200ltr receiver tank.

KEY FEATURES

- Direct drive transmission for improved power transfer
- Variable speed 5.5kW motor delivers even power distribution
- Heavy-duty silenced cabinet ensures reduced noise operation
- Colour touchscreen for real-time diagnostic information
- Easy access cabinet panel for maintenance and service
- All-in-one design minimises lost work area space

2-Year Standard Silver Warranty*







The SIP QT 50/10 is part of the SIP QTAir Very Low Noise range, using an innovative quiet system that allows top performance and high-quality air production with 59dB reduced noise in all environments.

Ideal for a range of applications where powerful performance must be balanced with reduced noise without compromise.

KEY FEATURES

- · Innovative quiet system for reduced 59dB operating noise level
- · Slow-running 4-pole brushless induction motor for longer life
- · Oil-free system for high-quality and clean air supply
- · Fan-cooled twin cylinder motor and pump units



Motor Power:	1.3hp (1kW) 4-POLE	
Receiver Size:	50ltr	
Piston Displacement:	7.30CFM (206ltr/min)	
Free Air Delivery (FAD):	5.40CFM (153ltr/min)	
Max. Air Pressure:	145psi (10bar)	







SIP QT 100/10 Compressor Low Noise Direct Drive

The SIP QT 100/10 is part of the SIP QTAir Very Low Noise range, using an innovative quiet system that allows top performance and high-quality air production with 59dB reduced noise in all environments.

Ideal for a range of applications where powerful performance must be balanced with reduced noise without compromise.

KEY FEATURES

- Innovative quiet system for reduced 59dB operating noise level
- · 2x slow-running 4-pole brushless induction motors for longer life
- · Oil-free system for high-quality and clean air supply
- · 2x fan-cooled twin cylinder motor and pump units

Motor Power:	2x 1.3hp (1kW) 4-POLE	
Receiver Size:	100ltr	
Piston Displacement:	14.60CFM (413ltr/min)	
Free Air Delivery (FAD):	10.80CFM (306ltr/min)	
Max. Air Pressure:	145psi (10bar)	
Noise Level:	59dB	

Conversion Factors

FROM OLD UNIT	TO SI UNIT	CONVERSION
LENGTH		
Inch (in)	Millimetres (mm)	x25.4
n/16 inch	Millimetres (mm)	x1.6
Foot (ft)	Metres (m)	x0.305
mile (mi)	Kilometres (km)	x1.609
MASS		
Pound (lb)	Kilogramme (kg)	x0.454
Ounce (oz)	Gramme (g)	x28.04
Long Ton (UK)	Tonne (t)	x1.02
Short Ton (USA)	Tonne (t)	x0.91
FORCE (WEIGHT)		
Pound-force (lbf)	Newton (N)	x9 then ÷2
TORQUE	Nauton Metro (N. rr.)	v4.26
Foot Pound Force (lbf ft)	Newton-Metre (N m)	x1.36
PRESSURE		
lbf/in² (psi)	Bar	÷14.5
Bar	Kilopascal (kPa)	x100
lbf/in² (psi)	Kilopascal (kPa)	x6.9
kgf/cm² or kp/cm²	Bar	x0.98
Atmosphere (standard)	Bar	x1.013
Inches Water Gauge (inH ₂ 0)	Millibar (mbar)	x2.49
Millimetres of Mercury (mmHg) (Torr)	Millibar (mbar)	x1.33
Tons/in ²	Bar	x154
VOLUME		
Gallon (UK) (gal)	Litre (L)	x4.54
Gallon (USA) (gal)	Litre (L)	x3.79
Pint (UK) (pt)	Litre (L)	x0.57
Pint (USA) (pt)	Litre (L)	x0.47
Fluid Ounce (UK) (fl oz)	Cubic Centimetre (cm³)	x28.4
Fluid Ounce (USA) (fl oz)	Cubic Centimetre (cm³)	x29.6
FLOW		
Cubic Feet Per Minute (cfm)	Cubic Decimetres/Second (dm³/s) (ltrs/sec)	x0.472
Cubic Feet Per Minute (cfm)	Cubic Metres/Second (m³/s)	x0.472 then ÷1000
Cubic Feet Per Minute (cfm)	Cubic Decimetres/Minute (dm³/s) (ltrs/min)	x28.32
POWER		
Horsepower (hp)	Watt (W)	x746
Horsepower (hp)	Kilowatt (kW)	x0.746
ENERGY, WORK		
Foot-Pound-Force (ft lbf)	Joule (J)	x1.35
Kilogramme-Force Metres (kgf m)	Joule (J)	x9.807
British Thermal Unit (Btu)	Joule (J)	x1055
TEMPERATURE		
Fahrenheit (°F)	Celsius (°C)	+40 then x5 then ÷9 then -40

のロスタ



ambersi

BAND-IT®







Finger Lakes Extrusion













Bonomi

品





































































LUDECKE







































RHODES









































Address

Unit 5 Seawall Court Seawall Road Cardiff CF24 5PQ



029 2046 5451



info@bspsales.com



www.bspsales.com

20242025